



ICP201G/N - RATIONAL iCombi Pro - Model 20-1/1 - Natural Gas Freestanding Combi Oven - 42 kW The intelligent RATIONAL iCombi Pro 20-1/1 thinks, learns, watches and adapts, dynamically responding to requirements.

- Large 20 x GN 1/1 capacity, ideal for mass catering and for food service establishments with high output requirements
- Four intelligent assistants for climate management, cooking operation, production management, and cleaning
- iDensityControl delivers consistent and uniform results. At the same time, the intuitive operating concept provides the highest level of user support and less chance of errors
- iCookingSuite continuously checks the condition of the food against the desired result, calculates the cooking progress and intelligently adjusts the temperature to achieve. It also allows you to change the desired result, browning or cooking parameters during the cooking process

- iProductionManager optimises food production, simply place the dish on the display and it will show you what else you can produce at the same time
- iCareSystem 9 cleaning programmes, including the ultrafast interim clean in approx. 12 minutes
- WiFi interface for connected cooking and easy access to HACCP documentation

Specifications					
Summary		Power and Performance			
Brand	Lincat	Total Power kW	42		
Range	RATIONAL	Temperature Range °C	30-300		
Series	iCombi Pro	IP Rating	IPX5		
Power Type	Gas	Temperature Control	Electronic		
Gas Type	Natural Gas	Oven Rating kW	Steam connection = 38.0; Hot air		
Unit Type	Free-standing		connection = 42.0		
Available in UK Only	Yes				
UK Warranty	RATIONAL 2 Years Parts and Labour Warranty				
Key Specifications		Capacity			
Type of Lighting	LED	Gastronorm Capacity	20 x GN1/1		
Number of Grids included	0	Portions per Day	150-300		





Weights and Dimensions		Supply Connections	Supply Connections	
Unit Height (External) mm	1872	Requires Installation	Yes	
Unit Width (External) mm	877	Requires Electrical Supply	Yes	
Unit Depth (External) mm	913	UK 3 Pin Plug	Yes	
Net Weight Kg	284	Requires Hardwiring	No	
		Electrical Supply Rating Watts	1,300	
		Single Phase Amps	13	
		Single Phase Voltage	230	
		Gas Connection BSP	3/4"	
		Gas Pressure Natural mbar	18-25	
		Total heat input at full rate Natural kW	42	
		Water Connection Pressure Bar	6	
		Drain Connection	DN 50 mm	
		Water Connection	3/4"	

Shipping

 Packed Weight Kg
 312.4

 Packed Height cm
 204.3

 Packed Width cm
 100.8

 Packed Depth cm
 101.3

Available Accessories

60.70.464

RATIONAL Applicance Connection Kit - Model 6-1/1-20-2/1 - with Adapter for Model XS $\,$



Lincat Limited Customer Care

Whisby Road, **Tel:** +44 1522 875500

Email: care@lincat.co.uk

Lincoln, LN6 3QZ, United Kingdom

Company No: 2175448

A member company of

Care Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday – Friday:

8.30am - 5pm