

# OPAL REMOTE COUNTER TECHNICAL DATASHEET

## O2R OPAL TWO DOOR REMOTE COUNTER



O2R

Dimensions (mm)	External	Internal
Width	1231	870
Depth	700	585
Height	887	600
Door Opening		390
<b>Capacity</b>		
Capacity cu.ft/ltrs		13.2/374

## O3R OPAL THREE DOOR REMOTE COUNTER



O3R

Dimensions (mm)	External	Internal
Width	1711	1350
Depth	700	585
Height	887	600
Door Opening		390
<b>Capacity</b>		
Capacity cu.ft/ltrs		19.2/545

## KEY FEATURES

- Foodsafe stainless steel exterior and interior
- Radiused, easy clean, interior based corners
- Self closing doors
- Barrel locked doors
- Magnetic balloon door gaskets with 100% tight seal
- Fitted with 2 of 1/1GN nylon coated wire shelves per section as standard or trayslides to accommodate 1/1GN containers
- Anti-tilt trayslides
- Removable racking system

- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential).
- Adjustable stainless steel 304 legs with flange for deck fixing
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 43°C ambient
- High performance helium leak testing
- Connection to third party supervisory communication systems such as BMS is possible using proprietary equipment. Please contact Williams for more information.

## OPTIONS

- Additional shelving / trayslides
- Drawer banks (2 or 3)
- Screw on splash-back



# OPAL REMOTE COUNTERS TECHNICAL DATA

	HO2R	LO2R	HO3R	LO3R
Temperature (°C)	+1/+4°C	-18/-22°C	+1/+4°C	-18/-22°C
Power Supply	230V/50Hz/1Ph			
Fuse (Amps)	13	13	13	13
Defrost	Off-cycle	Electric	Off-cycle	Electric
<b>Fittings</b>				
Shelves	4	4	6	6
Trayslides per door	4	4	4	4
<b>Electrical / Energy Data - Standard Refrigerant</b>				
Refrigerant	R134a	R452A	R134a	R452A
Running (Amps)	0.5	0.5	0.5	0.5
Required Refrigeration Capacity	320W*	335W**	320W*	335W**

## IMPORTANT NOTES:

\*Evaporating at -10°C within a 32°C Ambient

\*\*Evaporating at -30°C within a 32°C Ambient

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration  
Bryggen Road,  
North Lynn Industrial Estate  
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000  
Spares: +44(0) 1553 817 017  
E info@williams-refrigeration.co.uk  
W www.williams-refrigeration.co.uk

