


Demand more. Choose Foster

EcoPro G2 600 Litre Upright Freezer Cabinet EP700L



Temperature



Dimensions (mm)



Capacity

600 Litres

Weight

Unpacked: 121 KG Packed: 133 KG

Features & Benefits

We've revolutionised professional refrigeration... again. Built from the ground up to include over 50 new features and innovations, the EcoPro G2 is loaded with new design, quality, reliability efficiency and performance features.

- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair
 Il air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet

External Finish			
304 Stainless Steel	Option		
Stainless Steel	Standard		
304 Stainless Steel Rear	Option		
For Island Siting			

Internal Finish	
304 Stainless Steel	Option
Aluminium	Standard

ononing	
GN 2/1	Quantity: 3 Standard
Shelf	
Additional	Option
Shelf	

l	Base Fittings	
	80mm Castors	Standard
	150mm Legs	Option

Doors		
Solid Full	Standard	
Solid Half	Option	
Hinged - Right Hand	Standard	
Hinged - Left Hand	Option	

Refrigeration		
Forced Air	Standard	
Integral	Standard	
R290 (Hydrocarbon)	Standard	
R404a	Option	
Drain Required?	No	

Electrical, Energy and Service Information			
230 Volts	Standard		
50Hz	Standard		
60Hz	Option		
1 Phase	Standard		
Running Watts	1021		
Running Amps	4.2		
Thermal Heat Rejection (W)	1,031		
Noise (dBa @ 1m)	64.1		
Fuse Required (A)	10 amp		
Refrigerant charge	0.12		
Global Warming Potential	3		
Energy Efficiency Index	43.24		

Footnotes

- Marine kit option includes legs, bulkhead brackets & marine shelves.
- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm.
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.

Energy Performance Data and information



Application

This appliance is intended for use in ambient temperatures up to $40\frac{34}{3}$ C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit www.fosterrefrigerator.co.uk/Foster-OurPolicies.asp