

KFSD2N



PASTRY REFRIGERATOR 60x80 cm, ONE DOOR, POS.TEMP.

Exterior/interior in AISI304 18-10 s/steel.Ventil. cooling system with finned evaporator. Electronic thermometer/thermostat.Automatic defrosting system by hot gas,automatic evaporation of condense drain.AISI304 18-10 s/s handle and removable shelf supports. Single compartment 60x80 cm, one door.



General information

Supplier/producer 's name	SAGI
Series	Pastry & Bakery
Supplier's model identifier	KFSD2N
Category	vertical cabinet
Type	refrigerator
Line	pastry & bakery - EN 60x80

Technical features

Temperature ranges, °C	-2/+8
Energy Efficiency Class	D
Energy consumption E24, kW/h	2,36
Energy consumption/year, kW/h	1007
Method for energy consumption	EN 16825
Energy Efficiency Index	62,6
Net usable volume, lt	609
Volume, gross, lt	858
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R134a/1431
Refrigerant charge, kg	0,28
LWA dB(A)	56
Cooling system	ventilated refrigeration system
Defrosting	automatic "intelligent" defrosting by hot gas, which activates only when necessary

PASTRY REFRIGERATOR 60x80 cm, ONE DOOR, POS.TEMP.

ANGELO PO GRANDI CUCINE S.p.a. con socio unico
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy
www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 03/09/2018 18.39.54



KFSD2N



Evaporation of condense drain	automatic
Refrigeration power at -10°C W	447
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,39

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	diamond treated bottom with drain hole
Insulation thickness, mm	75
Door	1 door in AISI 304 stainless steel
Standard hinging door	on the right / reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	40/30
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	105 ÷ 155

Control and functions

Kinf of control	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	Hyper Cold - Energy Saving - setting of the relative humidity to 75% or to 90%

Standard

Key-lock	yes
Lighting	yes
Couple of guides (n.)	20 pair of AISI 304 stainless steel runners

Dimensions and weights

Packing (LxDxH), cm	89x106,5x213
Dimensions (LxDxH), cm	82x100x204
Gross Weight (kg)	180
Net Weight (kg)	162

PASTRY REFRIGERATOR 60X80 cm, ONE DOOR, POS.TEMP.

