



in association with



Inspired by Scandinavia

WMC622 Washing Machine

6

Kg Load



Steel Seal™



Active Drum™

390

G-Factor

Shortest cycle time

00:55

Super Quick Wash 60°C



Quick Overview

- Maximum spin speed: 1200 rpm
- Finish: Light grey
- 28 programmes including three custom programmes
- Anti-leakage system and child lock
- ECO cold and hot water connection - saves up to 70% of electrical consumption and 20% of the programme time
- Connection: 230V / 1ph / 10A / 50Hz
Max effect: 2.2kW
- Available with pump or valve drain system

Construction

Operating position: Front-operated

Capacity: 6kg

Door opening: 31cm

Door opening angle: 180°

Door opening: Left hinge

Material: Zync coated and painted housing
Stainless steel drum

Lifters in drum: Removable for easy cleaning

Base plate: Waterproof

Electrics

Connection power: 2,200W

Fuse: 10A

Electrical connection: 220-240V

Frequency: 50Hz

Length of power cable: 2.1m

Phases: 1

Connection of water/drain

Cold and hot water connection: Size 3/4"
(adapter 1/2" included)

Inlet hose: PEX inlet hose, able to withstand 10 bar at 95°C (tested to over 50 years)

Drainage capacity: 20l/min

Drain system: Drain valve or pump available

Dimensions

Dimensions (H x W x D): 850 x 595 x 585mm

Packaging dimensions: 920 x 640 x 660mm

Net weight: 79kg

Gross weight: 82kg

Adjustable feet: 10mm

Depth with door open: 965mm

Inlet hose, length: 1,500mm

Inlet hose: 1,600mm

WMC622 Washing Machine



Drain valve version shown



Properties
Balance control: Protects the washer against harmful vibrations
Foam control: Sensors detect foam levels and automatically begin to remove excess foam
Emergency opening function: Standard
Maximum inlet time: Machine stops if correct water level is not achieved within a specified time
Water overfill protection: Standard
Remaining operating time: Shown on digital display
Protection against overheating: Thermal and electronic

Performance
Residual humidity: 55%
Heater power: 2,000W
Temperature range: Cold - 90°C

Programmes		
Normal 60°C	Wool/Hand wash 30°C	Allergy cotton 60°C
Normal 40°C	Rinse	Allergy cotton 40°C
Heavy 90°C	Mop 60°C	Allergy synthetics 60°C
Heavy 60°C	Mop 90°C	Allergy synthetics 40°C
White 90°C	Microfibre 60°C	Cleaning
White/Colour 60°C	Microfibre 40°C	Customisable Programme A
White/Colour 40°C	Disinfection 1 + 20 min 40°C	Customisable Programme B
Super Quick wash 60°C	Disinfection 2 + 60 min 60°C	Customisable Programme C
Super Quick wash 40°C	Disinfection 3 + 10 min 90°C	
Synthetics 40°C	Allergy cotton 90°C	

Operations
Display type: LCD display
Language: DA, DE, EN, ES, FI, FR, IT, NL, NO, RU, SV
Dispenser: Manual pull-out
Detergent dispenser: Three compartment dispenser

Options
Communication interface (MODBUS)
Card payment system
Coin payment system
Relay card auto dose

DC Products

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: 01749 870055 e: sales@dcproducts.co.uk w: www.laundry.dcproducts.co.uk