



YF41102/B500 - FriFri Basic+ 411 Electric Freestanding Single Tank Fryer - 2 Baskets - W 400 mm - 22.0 kW

- Superb temperature control for consistently excellent results. Highly responsive digital electronic control able to maintain oil to +/-1 °C of the temperature selected
- Vertically coiled element for greater surface contact with oil, delivering fast recovery and preventing oil from scorching and degrading

High-performance frying has never been as easy as it is with the FriFri 22kW Basic+ 411 Free Standing Fryer.

- Integral gravity filtration extends oil life by up to 75% saving you money on oil purchase and disposal costs. Optional xFri® integrated oil pump and filtration system, increases efficiency, convenience and safety while extending oil life and saving you money
- Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning

Specifications

| Summary | | Power and Performance | |
|---------------------------|-----------------------------------|--------------------------------|---------------------------|
| Brand | FriFri | Total Power kW | 22.0 |
| Range | Basic+ | Temperature Range °C | 60-190 |
| Power Type | Electric | IP Rating | IP25 |
| Unit Type | Free-standing | Temperature Control | Electronic |
| Available in UK Only | No | | |
| UK Warranty | 2 Years Parts and Labour Warranty | | |
| Export Warranty | Contact your local dealer | | |
| GTIN | 5056105113331 | | |
| Key Specifications | | Capacity | |
| Number of Baskets | 2 | Product Output per Hour | 44kg fries - 7mm [frozen] |
| Number of Tanks | 1 | Capacity Litres | 17.0-20.5 |
| Gravity Filtration | Yes | | |
| Pumped Filtration | No | | |
| Drain Location | Through the body | | |
| Weights and Dimensions | | Supply Connections | |
| Unit Height (External) mm | 990 | Requires Installation | Yes |
| Unit Width (External) mm | 400 | Requires Electrical Supply | Yes |
| Unit Depth (External) mm | 650 | UK 3 Pin Plug | No |
| Net Weight Kg | 63.1 | Requires Hardwiring | Yes |
| | | Electrical Supply Rating Watts | 22,000 |
| | | Three Phase Amps | L1=31.9; L2=31.9; L3=31.9 |
| | | Three Phase Voltage | 400 |
| | | Number of Supply Cables | 1 |
| Shipping | | | |

| Packed Weight Kg | 69.41 |
|------------------|-------|
| Packed Height cm | 113 |
| Packed Width cm | 79 |
| Packed Depth cm | 52 |
| | |

baric+

| Available Options | | |
|-------------------|---|-----------|
| Oil Pump | | |
| OP1 | 1 Oil Pump | |
| - | | |
| Baskets | | |
| 411_1_BASKET | | 1 Basket |
| 411_2_BASKETS | | 2 Baskets |
| | | |
| Legs/Castors | | |
| OC200 | OC200 - 2 Castors [Fixed at Rear] + 2 Legs [at Front] | |
| OC400 | OC400 - 4 Castors [2 Fixed at Rear + 2 Swivel at Front] | |
| | | |

| Available Accessories | |
|-----------------------|--|
| FZ100831 | SMALL BASKETS FOR 211 411 412 422 - COMPLETE WITH HANDLE |
| FZ411048 | LARGE BASKET FOR 411 - 5MM MESH - COMPLETE WITH HANDLE |
| OF2 | Oil filter kit - size 2 |

Lincat fift

Lincat Limited

Whisby Road, Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500 Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday – Friday: 8.30am – 5pm